

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>H04Q 3/00, H04M 15/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 97/23102</b> <b>(43) International Publication Date:</b> 26 June 1997 (26.06.97)
<b>(21) International Application Number:</b> PCT/US96/20574 <b>(22) International Filing Date:</b> 20 December 1996 (20.12.96)  <b>(30) Priority Data:</b> 08/576,073                      21 December 1995 (21.12.95)      US  <b>(71) Applicant:</b> ERICSSON INC. [US/US]; 7001 Development Drive, P.O. Box 13969, Research Triangle Park, NC 27709 (US).  <b>(72) Inventor:</b> HAYES, Stephen, R.; 2104 Via Madonna, Carrollton, TX 75006 (US).  <b>(74) Agents:</b> MOORE, Stanley, R. et al.; Jenkins & Gilchrist, P.C., Suite 3200, 1445 Ross Avenue, Dallas, TX 75202 (US).		<b>(81) Designated States:</b> AU, BR, CA, CN, JP, KR, MX, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
<b>(54) Title:</b> REAL-TIME NETWORK FOR DISTRIBUTED TELECOMMUNICATIONS ACCOUNTING SYSTEMS  <b>(57) Abstract</b> <p>A telecommunication switch serving a roaming mobile station transports the resulting billing records by setting up a communication link with an administrative billing center connected to a Signaling System No. 7 (SS7) telecommunications network by utilizing Signal Connection Control Point (SCCP) signals. Once the connection is established between the telecommunication switch and the administrative billing center, Data Message Handler (DMH) formatted data are stored into a Data Form 2 (DT2) SCCP signal by the telecommunication switch and transported to the administrative billing center via the SS7 telecommunications network.</p> <div data-bbox="609 1144 1291 1459"></div>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NI	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LJ	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

**REAL-TIME NETWORK FOR DISTRIBUTED TELECOMMUNICATIONS  
ACCOUNTING SYSTEMS**

**CROSS REFERENCE TO RELATED APPLICATION**

This application is related to U.S. Application for Patent Serial No. 08/576,572, filed December 21, 1995, entitled TRANSPORT MECHANISM FOR ACCOUNTING MESSAGES WITHIN A TELECOMMUNICATIONS SYSTEM (Docket No. 27943/00030).

**BACKGROUND OF THE INVENTION**

**Technical Field Of The Invention**

This invention relates to charging in a telecommunications network and, more particularly, to the use of SS7 protocols for transporting accounting messages.

**Description of Related Art**

Developments and improvements in wireless telecommunications switching systems have allowed wireless users to easily move from one geographic area to another and still access and utilize the user's own telephone services and subscriber features. One example of this type of service is roaming. Roaming allows the subscriber to move from one city covered by a first telephone company to another city covered by a second telephone company and still use his or her cellular telephone unit. Currently, telephone services toward a roaming subscriber are allowed after the second telephone company requests and receives confirmation data regarding the roaming subscriber's service from the first telephone company. After services have been provided to the roaming subscriber, the second telephone company collects the charging data and sends the

-2-

information, usually in a batch file, to a centralized administrative center for further analysis. It is at this point that the rightful owner or the centralized billing administrative system first discovers illegal use of the service by a clone. Since the transfer of the billing batch file is usually done a few days after the actual services have been provided to the roaming subscriber, there is an undesirable time delay before possible fraud is detected.

10 Cellular radio telephones fall into two main categories, namely mobiles and hand portables. Conventionally, each cellular telephone whether mobile or hand portable has its own unique telephone number by which it may be accessed from other cellular telephones or  
15 fixed-wired conventional telephones. The full telephone number is stored in a memory (e.g. a ROM, PROM, or RAM) known in the art as a number assignment module (NAM), that is coupled to the control circuits, usually a microprocessor, of the cellular telephone. When an  
20 infringer "steals" a valid cellular telephone number and duplicates the number in another cellular phone (i.e., cloning), the infringer is free to use the telephone service while incurring the charges to the rightful subscriber. Unfortunately, when the roaming subscriber  
25 is using the service without proper authority from the rightful owner of the service, the centralized administrative center or the rightful owner of the services is not notified of the illegal usage until the billing records from the second telephone company are  
30 received.

-3-

A number of security checks have been placed in the system to filter and detect fraudulent calls before they are made. However, it would also be a desirable capability for telecommunications networks to allow services to roaming subscribers while being able to detect fraud on the system on a substantially real time basis after the call is made. The term "real time" for the purposes of the present invention implies a situation where events are handled or notified with minimum time delay after they actually occur in the system. This capability would allow the networks to minimize illegal usage of telecommunication services by narrowing the gap between the time the service is provided to an infringer and the time the centralized administrative center receives the billing records and detects the fraud. This capability would also fully support features and services within the telecommunications network that require both billing records and normal telecommunications data at the same time.

20

#### SUMMARY OF THE INVENTION

Instead of using a tape drive or a separate network to transport charging records to a centralized administrative center, the present invention advantageously connects the administrative center of the cellular system as a node in the SS7 telecommunication network, and all charging records are transported from each local exchange to the administrative center by SCCP signals. Because of the hierarchical architectural and strict timing requirements required in SS7 telecommunications networks, the implementation of the

30

-4-

present invention allows the telecommunications network to continue providing existing telecommunications services to roaming subscribers while detecting illegal usage with minimum time delay. The present invention further allows  
5 the telecommunications network to provide and support subscriber features and telecommunications services that require both billing records and normal telecommunications data at the same time using the same network on a real-time basis.

10 In one aspect, the present invention provides a method and apparatus of handling accounting messages in the SS7 telecommunications network in which accounting messages are transported to the administrative billing center by SS7 SCCP signals.

15 In another aspect, the present invention provides a SS7 telecommunication network wherein one of the nodes connected to the SS7 telecommunication network is an administrative billing center and all billing records are transported to the billing center according to the SS7  
20 protocols.

#### BRIEF DESCRIPTION OF THE DRAWINGS

For a more detailed understanding of the present invention, for further objects and advantages thereof,  
25 reference can now be had to the following description, taken in conjunction with the accompanying drawings in which:

FIGURE 1 is a block diagram illustrating a public land mobile network;

-5-

FIGURE 2 is a block diagram illustrating a networking of local exchanges and transit exchanges servicing a roaming wireless subscriber;

5       FIGURE 3 is a block diagram illustrating how two local exchanges unify their billing records by sending their data stored in magnetic tape to a centralized administrative center;

10       FIGURE 4 is an logical diagram representing how two independent machines, like telecommunication switches, reconcile each other's data to properly communicate with each other;

FIGURE 5 is an logical diagram representing the seven layers of Open System Interface (OSI);

15       FIGURE 6 is a block diagram of a section of a SS7 telecommunications network;

FIGURE 7 is a block diagram illustrating how each local exchange is connected to the CCS-SS7 network;

FIGURE 8 is a logical diagram comparing the four levels of SS7 with the seven layers of OSI;

20       FIGURE 9 is a logical diagram representing how the data message handler (DMH) standard is interfaced with Remote Operations Service Element (ROSE) and Association Control Service Element (ACSE) signals for transporting Call Detail Records (CDR) records to a centralized administrative center as defined in the prior art;

FIGURE 10 is a block diagram illustrating the use of SS7 protocols to communicate charging information in accordance with the teachings of the present invention;

30       FIGURE 11 is a SS7 signal chart representing a sequence of signals generated to connect and disconnect a communication link between a local switch and an

-6-

administrative center over a common channel signaling (CCS) network; and

FIGURE 12 is a block diagram illustrating how SS7 telecommunications networks include the administrative center as one of its nodes in order to communicate with other local switches in accordance with the teachings of the present invention.

#### DETAILED DESCRIPTION OF EMBODIMENTS

FIG. 1 shows a public land mobile network 10 in which the present invention, as will be disclosed herein, may be implemented. The public land mobile network (PLMN) 10, which is used to communicate with a mobile user, comprises a Mobile Services Switching Center (MSC) 40, a Home Location Register (HLR) 30, a base station (BS) 50 and a mobile station (MS) 80. The PLMN 10 is interfaced with a public switched telephone network (PSTN) 20 to provide a communication link to other telephone subscribers. This interface can be made at local, transit or international gateway levels. The BS 50 is connected to the MSC 40 using a digital or analog communications link 60, and communicates with a mobile station via a radio channel 70. The HLR 30 is a data base containing information about all subscribers, their services and location. In large networks with high subscriber densities, HLRs 30 are separate nodes. In small networks, they can be integrated in the MSC 40 as shown in FIG. 1. The BS 50 provides the communication link with a mobile station 80 when the mobile station is within one of the BS's coverage area known as a cell. The MSC 40, which contains the mobile station's 80 subscription, is labeled as the "home MSC."



-7-

If the subscriber crosses the border to another MSC area during a conversation, an interexchange handoff will take place and the adjacent MSC, known as a "visited MSC," then handles the conversation - this process is known as  
5 "roaming." Furthermore, if the mobile station 80 moves to another MSC area and tries to use its telecommunications service, the newly visited MSC notifies the home HLR 30 and requests confirmation data, and accordingly provides the telecommunications service to the  
10 visiting mobile station 80 - this process is also known as "roaming."

A call from the mobile subscriber starts when the mobile subscriber first keys the desired destination number and then presses the send button. If the mobile  
15 subscriber is within its home switch coverage area, an access channel is seized, whereupon the mobile identity and the desired number are automatically transmitted to the MSC 40 via the BS 50. The MSC 40 analyzes the calling subscriber's category to verify that the caller is  
20 permitted access to the system. The keyed destination number is also analyzed to determine if the caller is allowed to call that particular number. If all analyses are affirmative, the mobile subscriber is assigned to an analog or digital voice channel 70 and the call is set up.

25 However, if the mobile subscriber is outside of his own MSC coverage area and is roaming in a new MSC area, the mobile station automatically registers with the new MSC controlling the current area when the cellular unit is turned on. The visited MSC checks whether this mobile  
30 station is already registered. If not, the visited MSC informs the home MSC 40 or HLR 30 about the new position

-8-

of the mobile station. The home MSC 40 or HLR 30 notes in which service area the mobile station is roaming to be able to reroute all incoming calls to the new MSC. The roaming subscriber may now originate and receive calls in the same manner as that used in the home MSC. All special services (call transfer, call waiting, etc.) also automatically follow the roamer. The actual destination number and access validation do not occur until the roaming subscriber dials the destination number. If the mobile station has roamed from a previously visited MSC to a newly visited MSC, or back to the home MSC, the home MSC notifies the previously visited MSC to clear any data regarding that mobile from its visitor's register.

FIG. 2 is a block diagram illustrating a layout of local exchanges connected to each other in a telecommunications network. A mobile station (MS) 80 connects to the telecommunications network via a Mobile Serving Switching Center (MSC) 40A which is included within a Dallas local exchange 10A. The Dallas local exchange 10A further includes an HLR 30 as also shown in FIG. 1 that keeps track of the status and location of MS 80. When MS 80 dials a destination subscriber 90 connected to a Los Angeles local exchange 10B, a number of transit exchanges such as transit exchanges 90 route the call accordingly to interconnect MS 80 with the subscriber 85.

If MS 80 ever drives to New York and tries to use its phone, a MSC 40B attached to a New York local exchange 10C classifies the MS 80 as a roamer and requests user validity and subscriber data information from the roamer's Dallas local exchange 10A. Once the validation and the

-9-

necessary data have been received from the home switch, the MS 80 is allowed to use its service.

FIG. 3 is a block diagram of how billing records are generated and consolidated when a mobile station uses more than one local exchange during roaming. When a MS 80, assigned to home MSC 40A, tries to use its telephone service while roaming in an area covered by another local exchange 10C served by a visited MSC 40B, the visited MSC 40B requests validation and subscriber data information from the home switch 10A via PSTN comprising transit exchanges 90. The home switch 10A, in turn, updates the HLR 40A and sends the necessary data back to the visited MSC 40B via the same PSTN comprising transit exchanges 90. Once the MS 80 completes a call to another subscriber such as a subscriber 90 connected to yet another local exchange 10, Call Detail Records (CDRs) are produced by the visited MSC 40B. The CDRs are then sent off to a centralized administrative center 140 for further processing where other CDRs are also received from other local exchanges and consolidated bills 150 are generated for each individual subscriber. These CDRs are usually produced and outputted to magnetic tape 120 by charging subsystems (CHS) 100 and file management subsystems (FMS) 100 within the local exchanges 10A and 10C and physically delivered to the Administrative center 140 via magnetic tapes 120.

This delivery has traditionally been batch oriented; however, recent trends have been to provide message oriented accounting services. Consequently, as an alternative, these CDRs have been transported using a separate network 130 where all the CDR data are packetized and sent over the network 130 to the administrative center

-10-

140. Data Message Handler (DMH) is an example of such a standard. It is an interim standard (IS-124) developed by the Telecom Industry Association (TIA) for the exchange of accounting information between network providers.

5        Maintaining and utilizing this separate network 130 is unreliable, expensive and restrictive. It is unreliable because usually the network has a single node and a single unsupported communication link to connect each local exchange. It is expensive since a separate  
10 network has to be maintained to connect all the local switches with the centralized administrative center 140. Furthermore, as the number of connections representing local switches grows, the complexity and the cost of maintaining such networking becomes an insurmountable  
15 task. Finally, it could be restrictive if the local switches are only allow to access the network during certain time frame or have to share the network with another system.

As a result, if an infringer is using a clone mobile  
20 station to make illegal calls, these activities are not detected right away because of the time delay before those CDRs are received by the administrative center either by tape or packets.

FIG. 4 is a logical diagram representing how two  
25 independent computers, perhaps comprising telecommunications switches, synchronize and reconcile their data in order to communicate with each other. In a typical telecommunication network, there are virtually limitless local exchanges and other support computers  
30 interconnected with each other to provide telecommunication services to the subscribers. These

-11-

local exchange switches and computers are manufactured by different vendors and each may have its own protocols and specifications. Each computer, and each application program in the computer, may require a different communication access method and protocol (i.e., a standard convention for communicating intelligently) for a viable "conversation" to proceed. This sets very specific requirements on either or both parties to the conversation. In essence, the data must be presented to the end user in a form that they can recognize and manipulate. This may also involve protocol conversion to accommodate an end user's format, code, and language syntax.

As an illustration, due to developments and improvements in digital processing, telecommunications networks now support video and other interactive customer features as well as normal voice communication. In this videotex service, the supplier usually maintains a database or multiple databases on a variety of subjects of potential interest to customers; travel information, plane/hotel reservation information, shopping information, and so forth. Much of this information is in visual form and is delivered to the customer's terminal in a prescribed graphics format. The two parties to a "conversation" or session, the supplier and the customer, must first agree to set up a session through a network (or series of networks). They must agree on the format of the data ultimately delivered to the screen of the customer's terminal. If the sequence of bits delivered to the terminal in packet makes no sense to that terminal, even if the packet is delivered correctly, nonsense will appear

-12-

on the screen. The terminal must also be able to regulate the rate of delivery of data; otherwise the source computer that controls the source database could overwhelm the terminal. If connectionless transmission is used, packets may arrive out of order and the recipient terminal must be able to resequence these packets. All of these tasks and others like them have nothing to do with the physical operation of the network. The network may be delivering packets correctly and to the right place, and yet the overall system may not be performing properly. Therefore, it has become common to carry out a sequence of required tasks in an organized fashion, giving rise to the concept of layered communication architectures as shown in FIG. 4.

The above problems have led the International Organization for Standardization (ISO) to launch an intensive effort to develop a worldwide communication architecture standard that would allow different systems to communicate openly and resulted in Reference Model for Open Systems Interconnection (OSI). This architecture and others like them recognize that there are essentially two parts to the complete communications problems; (a) that of timely and correctly delivering data to the right place in the network, and (b) that of delivering recognizable data to both end users engaged in a conversation or session over a network or series of networks.

A number of "network protocols" have been developed to handle the first part of the problem. The second part is solved by introducing "higher-level protocols". Desirably, a complete end-user-oriented architecture encompasses both kinds of protocols. Accordingly, FIG.

-13-

4 portrays communication between an end user A 190A and  
an end user B 190B as an example in terms of this  
characterization. An intermediate network node 200 in the  
network is shown as well. This node could also have end  
5 users connected to it. However, the purpose of the  
intermediate node, so far as other network users are  
concerned, is only to provide the appropriate network  
services. Therefore, network services 170 in the source  
node 160A and corresponding network services 170 in the  
10 destination node 160B communicate with each other to allow  
the data to be transmitted and received at the destination  
correctly and in timely fashion. High level protocols 180  
in the source node 160A and corresponding high level  
protocols 180 in the destination node 160B ensure that the  
15 data ultimately delivered to the end user at the  
destination by the network services are recognizable and  
in the proper form for their correct use.

Moreover, the two groups - protocols providing  
network services and higher-level protocols - are  
20 typically broken down further into a series of levels or  
layers chosen to provide a particular service in terms of  
the basic problems just described: delivering data  
correctly, on time, and in recognizable form. More  
precisely, through the development of the OSI reference  
25 Model, the concept has developed of having each layer  
provide a service to the layer above it.

Accordingly, there are seven different layers in OSI.  
As shown in FIG. 5, they are the Application Layer 260,  
Presentation Layer 250, Session Layer 240, Transport Layer  
230, Network Layer 220, Data Link Layer 210, and Physical  
30 Layer 200.

-14-

As the highest layer in the Reference Model of OSI, the Application Layer 260 provides a means for the application processes to access the OSI environment. Hence the Application Layer 260 is the sole means for the application or process to access the OSI environment and to serve as the interface between correspondent application-entities which are using the OSI to exchange meaningful information.

The Presentation Layer 250 provides for the representation of information that application-entities either communicate or refer to in their communication. The Presentation Layer 250 covers two complementary aspects of this representation of information: (a) the representation of data to be transferred between application entities; and (b) the representation of the data structure which application-entities refer to in their communications, along with the representation of the set of actions which may be performed on this data structure. However, the Presentation Layer is concerned only with the syntax (i.e. the representation of the data) and not with its semantics (i.e. their meaning to the Application Layer) which is known only by the application-entities.

The purpose of the Session Layer 240 is to provide the means necessary for cooperating presentation entities to organize and synchronize their dialogue and to manage their data exchange. To do this, the Session Layer 240 provides services to establish a session connection between two presentation entities, and to support orderly data exchange interactions.



-15-

The Transport Layer 230 provides transparent transfer of data between session-entities and relieves them from any concern with the detailed way in which reliable and cost effective transfer of data is achieved. Therefore,  
5 the Transport Layer 230 optimizes the use of the available network service to provide the performance required by each session entity at minimum cost.

The Network Layer 220 provides the means to establish, maintain and terminate network connections  
10 between open systems containing communication application entities and the functional and procedural means to exchange network-service data units between transport entities over network connections. It provides to the transport entities independence from routing and relay  
15 considerations associated with the establishment and operation of a given network connection. This includes the case where several subnetworks are used in tandem or in parallel. It makes invisible to transport entities how underlying resources such as data link connections are  
20 used to provide network connections.

The Data Link Layer 210 provides functional and procedural means to establish, maintain and release data link connections among network entities and to transfer data link service data units. A data link connection is  
25 built upon one or several physical connections. The Data Link Layer 210 also detects and possibly corrects errors which may occur in the Physical Layer 200.

Lastly, the Physical Layer 200, which is the lowest and most hardware dependent layer in OSI, provides  
30 mechanical, electrical, functional and procedural means

-16-

to activate, maintain and de-activate physical connections for bit transmission between data link entities.

However, the fact that a system is "open" does not imply any particular systems implementation, technology  
5 or means of interconnection, but refers to the mutual recognition and support of the applicable standards. Therefore, it is not the intent of OSI either to serve as an implementation specification, or to be a basis for appraising the conformance of actual implementations, or  
10 to provide a sufficient level of details to define precisely the services and protocols or the interconnection architecture. Rather, ISO provides a conceptual and functional framework which allows users to work productively and independently on the development of  
15 standards for each layer of the Reference Model of OSI. Accordingly, each network has to develop its own set of detailed specifications conforming to the OSI model to actually achieve compatible telecommunication network.

In the United States and worldwide, the most widely  
20 accepted OSI standard for telecommunications communication has been Common Channel Signaling (CCS). In the telecommunications field, there are basically two different ways of sending various signaling messages in order to connect User A with User B. In the traditional  
25 telephone mode, referred to as inband signaling, signaling messages are sent over the same trunks as the information messages or calls themselves. In recent years, telephone networks have begun to introduce common-channel signaling, in which control messages or signals are carried over  
30 separate signaling channels. In the United States, in particular, this had led to the use of a separate packet-

-17-

switched network called the Common Channel Signaling (CCS) network for transmitting call setup and routing packets, as well as other supervisory and control information. However, CCS does not necessary require a separate network  
5 as signals could just as well be sent using dedicated signaling slots of a Time Division Multiplexing (TDM) frame.

With the advent of digital switching, CCS has rapidly become the preferred way of handling the connection of  
10 calls in circuit-switched networks. The objectives of CCS are to provide significant improvements in call connect time and considerably increased signaling capacity. These are made possible by modern digital techniques, the widespread use of computer controlled digital systems and  
15 by the availability of wide-band transmission facilities.

As mentioned briefly before, a separate signaling network may be used for CCS, or signaling may be done using the same physical facilities of the circuit-switched network, occupying separate channels (commonly time slots  
20 of a TDM frame) set aside for this purpose. Since signaling messages themselves are packets or short blocks of data, common-channel signaling has developed using packet-switched technology. A telephone network that adopts CCS as its method of handling the setting up and  
25 tearing down of circuit-switched calls thus uses two technologies: circuit switching for the calls themselves; and packet switching for the control messages required to handle the connection and disconnection of calls. The most commonly used technology for implementing CCS has  
30 been the Signaling System No. 7 (SS7) created by the CCITT.

-18-

The International Telephone & Telephone Consultative Committee (CCITT) is a UN treaty organization made up of the postal, telegraph and telephone authorities of member countries. CCITT works closely with ISO in the development of standards for communications. A CCS system developed by the CCITT and adopted as a recommendation in 1981 is called the CCITT Common Channel Signaling System No. 7, or simply Signaling System No. 7 (SS7). It is rapidly becoming recognized as the international standard.

This CCS signaling system, designed using the concepts of packet switching and tailored to conform with the OSI model, has been developed for use with both national and international traffic, for local and long-distance networks, for interexchange signaling, and for various types of channels, including both terrestrial and satellite channels. Furthermore, the introduction of a packet-switched network used to carry call-signaling messages makes other data-handling services possible as well. These services include the simultaneous transmission of various types of traffic, data, voice and video, among others. They make available the possibility of special types of call services such as "800" call features and services, call forwarding, calling party identification and other database administrations.

FIG. 6 is a illustrative diagram representing a section of a normal SS7 telecommunications network. To carry out the routing and signaling function, messages must be sent via the packet-switched signaling network from a local exchange A 10A to a local exchange B 10C. Signal Transfer Points (STPs) 270 either located at an exchange or geographically separate, are designated to

-19-

provide the generation and transfer of signaling messages. One signaling channel 280 is shown associated with two local exchanges 10A and 10C. A voice channel 290 allowing "conversation" between the two exchanges is separately represented as shown. Messages involving the use of trunks (channels) that connect these two exchanges are in this case transmitted directly between them. However, signals relating to the local exchange A 10A and the local exchange B 10C may also be transferred via an intermediate STP 270A, as shown. This mode of operation is called a nonassociated one. Both modes of operation have been defined in SS7 and as a result provide great robustness and reliability since the failure of one link will not affect the overall performance.

Now referring to FIG. 7, the CCS - SS7 network as shown is fully connected for reliability and robustness. The United States is divided into 10 regions and each of the 10 regions has two interconnected duplicated STPs 270A and 270B. The regional STP 270A is augmented by the area STP 270B for reliability. The A-links 500 provide access to the network from a local switch 10A where the local switch 10A is also connected to both STPs 270A and 270B for reliability. The STPs such as 270A and 270C in the network are themselves interconnected by so called B-links 520, while duplicate STPs in a region are connected by C-links 510. Furthermore, SS7 is designed for 56-kbps and 64-kbps transmission capacities, which speed up the call-connect process, allow faster transmission of signaling messages, and enable capacity to be increased drastically.

-20-

The hierarchy of the CCS-SS7 architecture allows the addition of a new node or switch to the network with minor adjustments, and because each region is supported by two STPs and two A-links and B-links, it provides great reliability and robustness. If a STP or a link goes down, the network will automatically reroute the data and maintain its network reliability automatically. Also, because of its addressing mechanism and global title translation, data can be transmitted by a local switch without the local switch knowing exactly where the destination switch is located. Lastly, because of its transmission capacities, the data transfer rate is greatly increased and near real-time capability is achieved.

Now referring to FIG. 8, even though SS7 protocol is designed to conform with the OSI Reference Model, it does not fit the seven layers of OSI exactly. As shown in FIG. 8, there are less than seven layers in SS7. Basically, SS7 has two parts, a user part and a message transfer part. The user part comes in several varieties, each one corresponding to higher-layer protocols that enable user functions, possibly on dissimilar machines, to communicate with one another. Examples of such user parts include a Telephone User Part (TUP) 360 for basic telephone service, and an Integrated Service Digital Network (ISDN) User Part (ISUP) 350 for providing combined voice, data and video services. These user parts make use of the network delivery services provided by the Message Transfer Part (MTP) 300 which provides a connectionless (datagram-type) but sequenced transport service. The function block labeled Signal Connection Control Point (SCCP) 310

-21-

provides the conversion from the MTP 300 to the network service specified by the OSI model.

It is apparent from FIG. 8 that different user parts enter the OSI model at different points in the hierarchy. The ISUP 350, for example, deals solely with services within the network and hence appears in the network layer of the OSI. User parts residing within the network layer of the OSI, but requiring presentation, session, and transport features similar to those provided by the overall OSI model as shown in FIG. 5, obtain these from the Network-Application Service Part (N.ASP) levels which consist of the Transaction Capability Application Part (TCAP) 330 and the Intermediate Services Part (ISP) 320.

This SS7 network structure and the SS7 protocols are an enhancement and advantageous over the separate network used by local exchanges to transmit billing records to the administrative center as defined in the prior art. Consequently, the preferred embodiment of the present invention utilizes this SS7 network to transport CDR data to the administrative center to take full advantage of the benefits offered by the SS7 network.

The reason the above CCS-SS7 network and SS7 signals have not been used before for transporting billing records was because, historically, billing has always been considered the domain of data communications while SS7 is considered signaling. Because of this artificial distinction, SS7 was not considered as a transport protocol even though it filled many of the requirements for transporting invaluable data such as billing. As a matter of fact, the DMH standard calls for the use of a Non-Signaling Data Protocol where an application level

-22-

protocol such as Remote Operations Service Element (ROSE) sitting on top of transport mechanism such as X.25 defined by the CCITT is usually used for transporting the packetized data in a network, and Association Control Service Element (ACSE) signals are used to set up the conversation between the switch and the administrative center. Therefore, instead of discarding all existing standards and protocols used in transporting billing records, the present invention discloses a system where parts of the prior art's standards and protocols are used on top of the SS7 protocols to minimize the modification and changes to the existing SS7 network and to utilize and salvage the existing DMH standard.

FIG. 9 represents a logical diagram representing the interfaces between the different protocols the separate network uses to transport CDR data from a local switch to a centralized administrative center as defined in the prior art and partly salvaged according to the preferred embodiment of the present invention. In order to reconcile all CDRs received from a number of different local exchanges, a set of protocols and messages were created for distributed billing collection known as Data Message Handler (DMH). Under DMH, all the records that are produced have globally unique identifiers and sequence numbers that allow them to be correlated. The DMH standard was actually developed by the cellular industry to solve the settlement issues associated with roaming subscribers. The DMH standard defines a set of messages and procedures for exchanging those settlement messages. In the DMH standard, these data are defined using Abstract Syntax Notation One (ASN.1) and transported using a



-23-

separate application level protocol over an Open System Interface Network Service Part (OSI NSP) such as X.25 defined by the CCITT. ASN.1 itself was developed as a standard to provide a machine independent way of specifying data structure that needs to be transported from one machine to the other. Hence, the ASN.1 standard defines items such as how many bytes are required to encode integers, real-numbers and strings.

As has been noted, DMH further requires specifications for its data content and carrier or transport mechanism for transporting the messages from one node to another node in a network. Therefore, the DMH standard 550 is supported by two separate protocols; Association Control Service Element (ACSE) 560 and Remote Operations Service Element (ROSE) 570. ACSE signals are used to initiate connection setup and termination between two nodes, and ROSE signals are used to store the contents of the data for delivery to each other. Once the connection is established by ACSE signals, ROSE signals such as ROIV (ROSE Invoke), RORS (ROSE Result), ROER (ROSE Error), and RORJ (ROSE Reject) are used to store and to communicate the actual data according to the ASN.1 standard for delivery to the administrative center. The actual transporting is carried out by the OSI Network Service protocol such as X.25 over the physical network.

The present invention discloses a system where by replacing the ACSE, ROSE and X.25 protocols with corresponding parts in the SS7 protocol, the local switch can utilize the already existing CCS-SS7 network to transport the CDR data to the administrative center without incurring any additional costs. Such networking

-24-

takes the full benefit of the SS7 network by having the data delivered on a real time basis while being reliable, robust, organized and cost effective.

Accordingly, FIG. 10 represents a logical diagram showing how DMH messages 550 are interfaced with a SCCP 310 and to be transported by a MTP 300 in a CCS-SS7 telecommunications network according to the preferred embodiment of the present invention. DMH no longer uses ACSE signals using a separate network to transport the billing records to the centralized administrative center. The administrative center becomes one of the nodes supported by the STPs and fully connected to the CCS-SS7 telecommunications networks. DMH messages are interfaced with the SCCP 310 within each local exchange to setup and establish a connection and the CCS-SS7 MTP 300 is used as the physical medium for transporting the billing records from the local switch to the administrative center.

Since, the SCCP 310 currently does not support signals for handling billing records, a new set of signals may be needed to simulate the ACSE and ROSE signals onto SCCP signals. However, instead of creating a new set of signals to handle setup, disconnect, and transfer of billing records messages in the SS7 network, the following mapping between the existing SS7 signals and the ACSE and ROSE signals is preferred in the present invention:

-25-

Table 1: ACSE/ROSE to SCCP Message Mapping.

ACSE/ROSE SERVICE	SCCP MESSAGES	NOTE
ACSE services (Session setup / tear down services)	Connection Request (CR) / Connection Refused (CREF) / Released (RLSD) / Release Complete (RLC)	Only mandatory field is used.
ROIV (Invoke)	Data Form 2 (DT2)	Only mandatory DT2 fields used.
RORS (Result)	Data Form 2 (DT2)	Only mandatory DT2 fields used.
ROER (Error)	Data Form 2 (DT2)	Only mandatory DT2 fields used.
RORJ (Reject)	Error (ERR)	Spare codes used to map errors.
All DMH operations (aggregateDelivery, aggregateRequest, certifiedDelivery, rateRequest, recordRequest, retransmissionRequest, uncertifiedDelivery)	Data Form 2 (DT2)	

Accordingly as shown in Table 1, ACSE setup and disconnect signals are handled by the normal Connection Request and Released signals in the SS7 network. ROSE signals for actually delivering the data are handled by DT2 messages in the SS7 network. All other DMH operations such as requesting transmission rate (RateRequest) and

-26-

retransmission requests (RetransmissionRequest) are also handled by DT2 messages in the SS7 network. The benefit of the above mapping is to eliminate the need to introduce a new set of messages into the SS7 network and to reduce the modification that has to be made to the existing SCCP to accommodate the DMH operation.

FIG. 11 is an SS7 signal chart representing a sequence of signals to connect, deliver, and disconnect a communication link between the local switch 10A and the administrative center 10C through an intermediate node 270 according to the preferred embodiment of the present invention. As mentioned previously, according to the present invention, DMH no longer uses ACSE or ROSE signals to transport the data. The administrative center 10C is one of the nodes supported by the STPs and fully connected to the SS7 telecommunications network. When the local exchange 10A wishes to connect to the administrative center 10C to transport billing records, SCCP Connection Request (CR) 400 signal is transmitted toward an appropriate STP 270 or STPs 90. The STP 90, according to the global title translation table, relays the SCCP CR signal 400 to the correct destination. The administrative center 10C returns the connection request from the local switch 10A by returning a SCCP Connection Response signal 404 to the local switch 10A. Once the connection has been set up by both nodes, the local switch 10A encapsulates the billing data in a SCCP Data Form 2 (DT2) signal 408 and transmits it over the SS7 network to the administrative center 10C. The administrative center 10C returns the results of the data reception by storing a result code in a SCCP Data Form 2 (DT2) signal 408 and

-27-

transmits it back to the local switch 10A. After the completion of the transmission of the billing data, the local switch 10A releases the call connection by sending a SCCP Released (RLSD) signal 416 toward the administrative center 10C. Once the release request is received by the administrative center 10C, the center acknowledges and releases the physical connection and transmits the final signal, SCCP Release Complete (RLC) signal 420, back to the local switch 10A.

Although only one possibility for call release has been indicated, the protocol is symmetrical; either the calling party or the called party may initiate release via a Released signal 416. Release may also be initiated by any one of the nodes (switches) if it becomes congested. Furthermore, DTI messages can also be used instead to transport the billing data.

Now referring to FIG. 12, a layout of the SS7 telecommunications network having an Administrative Center 140 as one of its node served by STPs 270A and 270B is shown as the preferred embodiment of the present invention. As previously described during the description of FIG. 7, each node in the SS7 network, including the Administrative Center 140, is supported by dual STPs 270A and 270B and dual A-link communication line 500. Such networking guarantees the ambitious throughput and latency requirements required of capabilities such as advice of charging or fraud detection. Such networking also reduces the maintenance tasks required to support the routing information needed as the number of DMH nodes grow in the networks. The hierarchical routing available in SCCP provides a mechanism for resolving names, and the global

-28-

title translation can be used to simplify routing. Furthermore, the above networking provides the level of robustness required for transferring accounting information because the SS7 NSP provides many mechanisms  
5 for rerouting and network recovery to ensure the robustness of the network. Finally, the above SS7 networking also fully supports features that require both billing information and signaling information at the same time in a real-time basis (such as sophisticated advice  
10 of charge capabilities). This was not possible before because the signaling networks and accounting networks were two distinct networks in prior art. Including both accounting information and signaling information in the same SS7 network allows nodes to provide services that  
15 require both types of information at the same time (e.g. terminating a call if fraud is detected).

Although a preferred embodiment of the method and apparatus of the present invention has been illustrated in the accompanying Drawings and described in the  
20 foregoing Detailed Description, it will be understood that the invention is not limited to the embodiment disclosed, but is capable of numerous rearrangements, modifications and substitutions without departing from the spirit of the invention as set forth and defined by the following  
25 claims.

-29-

WHAT IS CLAIMED IS:

1. A system for communicating accounting messages within a telecommunications network, said system comprising:

- 5                   a switch node connected to said telecommunications network, said node providing telecommunications services to a telecommunications subscriber for which accounting messages are generated;
- an administrative center for collecting and
- 10                   analyzing accounting messages; and
- a communication link connecting said node to said administrative center over which said accounting messages generated by said node are transmitted to said administrative center in accordance with a Common Channel
- 15                   Signaling System No. 7 (SS7) Signal Connection Control Part (SCCP) protocol.

2. The system of claim 1 wherein said switch node comprises:

- 20                   a first subsystem for formatting said accounting messages in accordance with a Data Message Handler (DMH) standard;
- a second subsystem for processing SCCP signals, said SCCP signals comprising:
- 25                   a first set of signals for establishing communication between said switch node and said administrative center over said communications link; and
- a second set of signals for carrying said first subsystem formatted DMH accounting messages; and
- 30                   a third subsystem for transmitting said SCCP signals over said communications link to said

-30-

administrative center using a Message Transfer Part (MTP) level of the Signaling System No. 7 protocols.

3. The System of claim 2 wherein said second set  
5 of signals includes a SS7 SCCP Signal Data Form 2 (DT2).

4. The System of claim 2, wherein said first set  
of signals for establishing communication simulates  
10 Association Control Service Element (ACSE) signals.

5. The System of claim 2, wherein said second set  
of signals for carrying said first subsystem formatted DMH  
accounting messages simulates Remote Operation Service  
15 Element (ROSE) signals.

6. The system of claim 1 wherein said  
administrative center comprises:

a first subsystem for receiving said SCCP  
20 signals over said communications link from said switch  
node using a Message Transfer Part (MTP) level of the  
Signaling System No. 7 protocols;

a second subsystem for processing said SCCP  
signals, said SSCP signals comprising:

25 a first set of signals for establishing  
communication between said switch node and said  
administrative center over said communications link; and

a second set of signals for receiving said  
accounting messages; and



-31-

a third subsystem for extracting said accounting messages from said second set of signals in accordance with a Data Message Handler (DMH) standard.

5           7.    The System of claim 6 wherein said second set of signals includes a SS7 SCCP Signal Data Form 2 (DT2).

8.    The System of claim 6, wherein said first set of signals for establishing communication simulates  
10   Association Control Service Element (ACSE) signals.

9.    The System of claim 6, wherein said second set of signals for carrying said first subsystem formatted DMH accounting messages simulates Remote Operation Service  
15   Element (ROSE) signals.

10.   A Common Channel Signaling System No. 7 (SS7) network system for transporting accounting messages, said network system comprising:

20           a plurality of nodes, wherein certain ones of said nodes generate Data Message Handler (DMH) formatted accounting messages;

          a plurality of communications links interconnecting said plurality of nodes;

25           a Signaling Connection Control Part (SCCP) module within each of said nodes for handling said DMH formatted accounting messages; and

          a Message Transfer Part (MTP) module within each of said nodes connected to said SCCP module for  
30   transmitting or receiving said DMH formatted accounting messages over said communications links.

-32-

11. The System of claim 10, wherein said certain ones of said plurality of nodes comprise a telecommunications switch, wherein said SCCP module generates SCCP signals, said SCCP signals comprising:

- 5           a first set of signals for establishing communication between said certain ones of said plurality of nodes and others of said plurality of nodes; and
- a second set of signals for carrying said DMH formatted accounting messages.

10

12. The System of claim 10, wherein one of said plurality of nodes is an administrative center for collecting and analyzing billing records, where said SCCP module receives SCCP signals, said SCCP signals comprising:

15

- a first set of signals for establishing communication between said certain ones of said plurality of nodes and others of said plurality of nodes; and
- a second set of signals for receiving said DMH formatted accounting messages.

20

13. The System of claim 11, wherein said set of signals for carrying said DMH formatted accounting messages comprise SS7 SCCP Signal Data Form 2 (DT2).

25

14. A method of transporting accounting data from a first node to a second node wherein said first node and second node are connected within a Common Channel Signaling System No. 7 (SS7) telecommunications network, said method comprises the steps of:

30

-33-

formatting said accounting data according to a common standard recognizable by said first node and said second node;

5 initiating setup from said first node to said second node within said SS7 telecommunications network using SS7 Signal Connection Control Point (SCCP) signals;

transporting said formatted accounting data from said first node to said second node within said SS7 telecommunications network using SS7 Signal Connection  
10 Control Point (SCCP) signals; and

disconnecting the connection from said first node to said second node within said SS7 telecommunications network using SS7 Signal Connection Control Point (SCCP) signals.

15

15. The method of transporting accounting data as claimed in claim 14 wherein said common standard comprises a Data Message Handler (DMH) standard.

20 16. The method of transporting accounting data as claimed in claim 15, wherein said step of transporting said DMH formatted data includes the step of interfacing with a Message Transfer Part (MTP) module of each node.

25 17. The method of transporting accounting data as claimed in claim 15, wherein said step of transporting said DMH formatted data includes the step of using SS7 SCCP Signal Data Form 2 (DT2) for storing the contents of said DMH formatted data.

30

-34-

18. The method of transporting accounting data as claimed in claim 14 wherein said first node comprises a telecommunications switch.

5        19. The method of transporting accounting data as claimed in claim 14 wherein said second node comprises an administrative billing center.

10       20. The method of transporting accounting data as claimed in claim 14, wherein said step of initiating setup further includes the step of interfacing with a Message Transfer Part (MTP) module of each node.

15       21. A system for transporting accounting data from a first node to a second node within a Common Channel Signaling System No. 7 (SS7) telecommunications network, wherein said system comprising:

      means for collecting and formatting said accounting data according to a Data Message Handler (DMH) standard within said first node;

      means for initiating connection setup from said first node toward said second node using SS7 Signaling Connection Control Part (SCCP) signals;

25       means for storing the contents of said DMH formatted data using SS7 Signaling Connection Control Part (SCCP) signals; and

      means for transporting said DMH formatted data stored in said SS7 SCCP signals from said first node to said second node.

30

-35-

22. A system for communicating accounting messages within a telecommunication network, said system comprising:

5 a telecommunications switch for providing telecommunications services;

an administrative billing center for collecting and analyzing said accounting messages;

10 a Common Channel Signaling (CCS) telecommunications network for connecting said telecommunications switch to said administrative billing center; and

a transport mechanism for carrying said accounting messages from said telecommunications switch to said administrative billing center over said CCS telecommunications network.

15

23. The system of claim 22 wherein said CCS telecommunications network comprises a Common Channel Signaling System No. 7 (SS7) protocol telecommunications network.

20

24. The system of claim 23 wherein said transport mechanism for carrying said accounting messages over said SS7 telecommunications network comprises Signaling Connection Control Part (SCCP) signals.

25

25. A telecommunications system comprising:

a plurality of telecommunications switches, each switch generating a set of signaling messages to provide telecommunications services, and generating accounting messages in response to the provision of said telecommunications services;

30

-36-

an administrative billing center for collecting and analyzing said accounting messages;



a Common Channel Signaling (CCS) network for interconnecting said plurality of telecommunications switches and said administrative billing center; and

a transport mechanism provided within each of said plurality of telecommunications switches for communicating said signaling messages between said plurality of telecommunications switches and for communicating said accounting messages from each of said plurality of telecommunications switches to said administrative billing center.

26. The system of claim 25, wherein said CCS telecommunications links comprises a CCS System No. 7 (SS7) protocol telecommunications link.

27. The system of claim 26, wherein said transport mechanism comprises signals, said signals transported over said CCS network in accordance with a Signaling Connection Control Part (SCCP) signaling protocol.

1 / 7



2 / 7




FIG. 2  
(PRIOR ART)



3 / 7




FIG. 3  
(PRIOR ART)

4 / 7




FIG. 5  
(PRIOR ART)






FIG. 6  
(PRIOR ART)



6 / 7




FIG. 9  
(PRIOR ART)

FIG. 10






FIG. 12

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 96/20574

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 H04Q3/00 H04M15/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04M H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 008 929 A (OLSEN ET AL.) 16 April 1991	1,22-27
A	see the whole document	2-21
A	--- PROCEEDINGS OF THE IEEE, vol. 80, no. 4, April 1992, NEW YORK, USA, pages 590-606, XP000304350 A.R.MODARRESI ET AL.: "An Overview of Signaling System No. 7" see the whole document	1-27
A	--- EP 0 544 449 A (AT&T) 2 June 1993 see abstract	1-27
	--- -/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*A\* document member of the same patent family

Date of the actual completion of the international search

16 May 1997

Date of mailing of the international search report

28.05.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+ 31-70) 340-3016

Authorized officer

Montalbano, F

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 96/20574

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>JAPAN TELECOMMUNICATIONS REVIEW, vol. 28, no. 3, July 1986, TOKYO, JAPAN, pages 163-171, XP002031041 HIROSHI SHIMUZU ET AL.: "New Automatic Message Accounting System" see page 2</p> <p>-----</p>	1-27

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 96/20574

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5008929 A	16-04-91	CA 2033880 A,C	19-07-91
EP 544449 A	02-06-93	AT 149780 T	15-03-97
		CA 2078195 A	28-05-93
		DE 69217845 D	10-04-97
		FI 925384 A	28-05-93
		JP 2552065 B	06-11-96
		JP 6069879 A	11-03-94
		US 5309501 A	03-05-94